



T5 Standard

28W/841 Min Bipin T5 HE ALTO UNP

Philips T5 Fluorescent Lamps featuring ALTO® Lamp Technology offer increased energy savings and low toxicity in a slim profile.

Product data

• General Characteristics

System Description	High Efficiency
Base	Miniature Bipin
Base Information	Green [Green Base]
Bulb	T5 [16 mm]
Life to 10% fail	19000 hr
Preheat EL,3h	
Rated Avg. Life	24000 hr
LSF HF Preheat	99 %
2000h Rated,3h	
LSF HF Preheat	99 %
4000h Rated,3h	
LSF HF Preheat	99 %
6000h Rated,3h	
LSF HF Preheat	99 %
8000h Rated,3h	
LSF HF Preheat	99 %
12000h Rated,3h	
LSF HF Preheat	97 %
16000h Rated,3h	
LSF HF Preheat	84 %
20000h Rated,3h	

• Light Technical Characteristics

Color Code	841 [CCT of 4100K]
Color Rendering Index	82 Ra8
Color Designation	Cool White
Color Temperature	4100 K
Luminous Flux EL	2625 Lm
25°C, Rated	
Luminous Flux EL	2625 Lm
25°C, Nominal	
Initial Lumens	2900 Lm
Lum Efficacy Rated	94 Lm/W
HF 25°C	

Lum Efficacy Rated	104 Lm/W
HF 35°C	
LLMF HF 2000h	96 %
Rated	
LLMF HF 4000h	95 %
Rated	
LLMF HF 6000h	94 %
Rated	
LLMF HF 8000h	93 %
Rated	
LLMF HF 12000h	92 %
Rated	
LLMF HF 16000h	91 %
Rated	
LLMF HF 20000h	90 %
Rated	
Design Temperature	35 C
Chromaticity Coordinate X	380 -
Chromaticity Coordinate Y	380 -

• Electrical Characteristics

Watts	28 W
Lamp Wattage EL	27.9 W
25°C, Rated	
Lamp Wattage EL	28 W
25°C, Nominal	
Lamp Wattage EL	27.8 W
35°C	
Lamp Voltage EL	166 V
25°C	
Lamp Voltage EL	167 V
35°C	
Lamp Current EL	0.170 A
25°C	

PHILIPS

T5 Standard

Lamp Current EL 0.170 A
35°C
Dimmable Yes

Insertion Length B 1153.7 (min), 1156.1 (max) mm
Overall Length C 1163.2 (max) mm
Diameter D 17 (max) mm

• Environmental Characteristics

Energy Efficiency A
Label (EEL)
Mercury (Hg) 1.4 mg
Content

• Measuring Conditions

Calibration Current 0.170 A
HF Generator Rated 329 V
Voltage
Resistor 950 ohm


• Product Dimensions

Base Face to Base 1149.0 (max) mm
Face A

• Product Data


Product number 230862
Full product name 28W/841 Min Bipin T5 HE ALTO UNP
Short product name 28W/841 Min Bipin T5 HE ALTO UNP/40
Pieces per Sku 1
eop_pck_cfg 40
Skus/Case 40
Bar code on pack 46677230869
Bar code on case 50046677230864
Logistics code(s) 927990684022
tpd_ilcos_cd FDH-28/40/1B-L/P-G5-16/1150
eop_net_weight_pp 104.500 gr

Dimensional drawing




28W/841 Min Bipin T5 HE ALTO UNP

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL5 HE F28T5/841 HE Alto	1149.0	1153.7	1156.1	1163.2	17




G5

Photometric data



Lightcolor /840



Lightcolor /840



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, April 10
data subject to change