

# High Output T12

#### F48T12 CW HO ALTO

Philips T12 fluorescent lamps provide high performance in a wide range of sizes, shapes, and types.

#### Product data

#### General Characteristics

Base R17d [Recessed Double Contact Bay

(RDC Bay-Fluorescent)]

Base Information Green Base Bulb T12
Rated Avg. Life [3 hr 12000 hr

Rated Avg. Life [3 hr Start]

Energy Saving

Not Applicable

### • Light Technical Characteristics

Color Code 33 Color Rendering 62 Ra8

Index

Color Designation Cool White Color Temperature 4100 K Initial lumen 4050 Lm Design Mean Lumens 3500 Lm

#### • Electrical Characteristics

Watts 60 W

#### • Environmental Characteristics

Mercury (Hg) 3.5 mg

Content

#### • Product Dimensions

Nominal Length 48

[inch]

#### Footnotes

Footnotes Fluorescent/CFL 207 [Approximate initial lumens are for 800 ma. operation. For 1000 ma. operation, lumens are approximately 10% higher and watts approximately

15% higher. (207)]

Footnotes Fluores-

cent/CFL

214 [Econ-o-watt® lamps are only recommended for use on high power factor lead, indoor ballasts that meet ANSI standards. The lamps are not recommended for use in drafty areas, or locations where the ambient temperature is less than 60°F, except as noted. Also they should not be operated on low power factor ballasts, reduced light or reduced current ballasts, dimming ballasts or emergency system inverter ballasts. (214)]

#### • Product Data

Product number Full product name Short product name Pieces per Sku eop\_pck\_cfg Skus/Case

Bar code on pack
Bar code on case
Logistics code(s)
eop\_net\_weight\_pp

369785 F48T12 CW HO ALTO F48T12 CW HO ALTO/15

1 15 15

46677369781 50046677369786 927890203305 0.001 kg



# High Output T12

## Dimensional drawing



T12 Recessed Double Contact F48T12 CW HO ALTO

