




GE
Lighting

23077 - F60T12/D/HO 15PK

GE Daylight T12



High Color Rendering



CAUTIONS & WARNINGS

Caution


- Lamp may shatter and cause injury if broken
 - Wear safety glasses and gloves when handling lamp.
 - Do not use excessive force when installing lamp.

Warning


- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution



Graphs_Lamp Mortality



GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Straight Linear
Bulb	T12
Base	Recessed Double Contact (R17d)
Rated Life (NOM)	12000.0 h
Bulb Material	Soda lime
Starting Temperature (MIN)	-29.0 °C
Mercury Content (NOM)	90.0 mg
Picograms of Mercury (NOM)	1958.2 pg
Primary Application	Full Wattage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	4400.0
Mean Lumens (NOM)	3830.0
Nominal Initial Lumens per Watt (NOM)	58.66667
Color Temperature (NOM)	6500.0 K
Color Rendering Index (CRI) (NOM)	75.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	75.0
Open Circuit Voltage (rapid start) Min @ Temperature	325 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	60.000 in(1524.0 mm)
Minimum Overall Length (NOM)	57.720 in(1466.1 mm)
Nominal Length (NOM)	60.000 in(1524.0 mm)
Bulb Diameter (DIA) (MIN)	1.410 in(35.8 mm)
Bulb Diameter (DIA) (MAX)	1.590 in(40.4 mm)
Bulb Diameter (DIA) (NOM)	1.500 in(38.1 mm)
End of Base Pin to End of Opposite Pin End (C) (NOM)	57.720 in(1466.1 mm)

PRODUCT INFORMATION

Product Code	23077
Description	F60T12/D/HO 15PK
ANSI Code	1014-1
Standard Package	Case
Standard Package GTIN	10043168230770
Standard Package Quantity	15
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	15
Package	
UPC	043168230773