6/11/2014 Product Details



Product 25128

Number:

Order F60T12/D35/HO

Abbreviation:

General 75W, 60"MOL, T12 HO (800 mA) rapid start fluorescent

Description: lamp, Designer rare earth phosphor, 3500K color

temperature, 70 CRI

Product Information

Abbrev. With Packaging Info. F60T12D35HO 30/CS 1/SKU

Actual Length (in) 57.720
Actual Length (mm) 1466.09
Average Rated Life (hr) 12000

Base Recessed Double Contact

Bulb T12
Color Rendering Index (CRI) 70
Color Temperature/CCT (K) 3500
Diameter (in) 1.593
Diameter (mm) 40.46
Family Brand Name Designer

Industry Standards ANSI C78.81 - 2001

 Initial Lumens at 25C
 5600

 Mean Lumens at 25C
 5040

 Mean Lumens at 35C
 5040

 Nominal Length (in)
 60.000

 Nominal Length (mm)
 1524.00

 Nominal Wattage (W)
 75.00



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.