


10835 - F72T8/WW 6PK

GE kitchen & bath 35 watt T8 1-pack

Lasts 3.4 years based on 6 hours per day usage

- 72 inches long
- 3000K warm white light appearance
- For use in kitchens, bathrooms, and living areas
- Warm, inviting light that complements any de#cor
- 1.0 inch diameter T8 with single pin (fa8) base

GE kitchen & bath fluorescent bulbs deliver a warmer tone to create a comfortable and inviting atmosphere.
These warm white bulbs are best for living areas throughout your home, hotels, commercial restrooms, reception areas and food preparation



CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning

Risk of Electric Shock

- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Graphs_Lamp Mortality



NOTES

Not for sale for use in OR

GENERAL CHARACTERISTICS

Lamp Type

Bulb Base Rated Life (NOM) Bulb Material Starting Temperature (MIN) Mercury Content (NOM) Picograms of Mercury (NOM) Primary Application Linear Fluorescent - Straight Linear T8 Single Pin (Fa8) 7500.0 h Soda lime 10.0 °C 90.0 mg 4255.3 pg Full Wattage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)3100.0Mean Lumens (NOM)2820.0Nominal Initial Lumens per Watt88.57143(NOM)Color Temperature (NOM)3000.0 KColor Rendering Index (CRI)52.0(NOM)Color Rendering Index (CRI)

ELECTRICAL CHARACTERISTICS

Wattage (NOM)35.0Open Circuit Voltage (instant
start) Min @ Temperature540 V @ 10 °CCathode Resistance Ratio - Rh/
Rc (MIN)4.25Cathode Resistance Ratio - Rh/
Rc (MAX)6.5Current Crest Factor (MAX)1.7

DIMENSIONS

Maximum Overall Length73(MOL) (NOM)Minimum Overall Length (NOM)63Nominal Length (NOM)73Bulb Diameter (DIA) (MIN)04Bulb Diameter (DIA) (MAX)14Bulb Diameter (DIA) (NOM)15Max Base Face to Base Face63(A) (NOM)74Face to End of Opposing Pin64(B) (MIN)64Face to End of Opposing Pin64(B) (MAX)64End of Base Pin to End of64Opposite Pin End (C) (NOM)64

72.000 in(1828.8 mm)

)	69.740 in(1771.4 mm)
	72.000 in(1828.8 mm)
	0.940 in(23.9 mm)
	1.100 in(27.9 mm)
	1.000 in(25.4 mm)
	69.300 in(1760.2 mm)
	69.420 in(1763.3 mm)

69.650 in(1769.1 mm)

69.740 in(1771.4 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

10835 F72T8/WW 6PK 3010-1 Case 10043168108352 6 Unit 1 6

043168108355