

High Output T12

F72T12 CW HO ALTO

Philips T12 fluorescent lamps provide high performance in a wide range of sizes, shapes, and types.

Product data

• General Characteristics

Base	R17d [Recessed Double Contact Bay (RDC Bay-Fluorescent)]
Base Information	Green Base
Bulb	T12
Rated Avg. Life [3 hr	12000 hr
Start]	
Energy Saving	Not Applicable

85 W

• Light Technical Characteristics

Color Code	33
Color Rendering Index	62 Ra8
Color Designation	Cool White
Color Temperature	4100 K
Initial lumen	6350 Lm
Design Mean Lumens	5500 Lm

• Electrical Characteristics

Watts

Environmental Characteristics

Mercury (Hg)	6.8 mg
Content	

• Product Dimensions

Nominal Length 72 [inch]

• Footnotes

Footnotes Fluorescent/CFL Footnotes Fluorescent/CFL 207 [Approximate initial lumens are for 800 ma. operation. For 1000 ma. operation, lumens are approximately 10% higher and watts approximately 15% higher. (207)] 214 [Econ-o-watt® lamps are only recommended for use on high power factor lead, indoor ballasts that meet ANSI standards. The lamps are not recommended for use in drafty areas, or locations where the ambient temperature is less than 60°F, except as noted. Also they should not be operated on low power factor

ballasts, reduced light or reduced current ballasts, dimming ballasts or emergency system inverter ballasts. (214)]

• Product Data

Product number Full product name Short product name Pieces per Sku eop_pck_cfg Skus/Case Bar code on pack Bar code on case Logistics code(s) eop_net_weight_pp 366518 F72T12 CW HO ALTO F72T12 CW HO ALTO/15 1 15 46677366513 50046677366518 927893203304 0.001 kg



Dimensional drawing



TI2 Recessed Double Contact F72T12 CW HO ALTO



 $\textcircled{\sc c}$ 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting