





GE
Lighting

11009 - F96PG17/CW

GE Cool White Power Groove® PG17



CAUTIONS & WARNINGS

Caution


- Lamp may shatter and cause injury if broken
 - Wear safety glasses and gloves when handling lamp.
 - Do not use excessive force when installing lamp.

Warning


- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution



Graphs_Lamp Mortality



GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Grooved
Bulb	PG17
Base	Recessed Double Contact (R17d)
Rated Life (NOM)	10000.0 h
Bulb Material	Soda lime
Starting Temperature (MIN)	-29.0 °C
Mercury Content (NOM)	4.95 mg
Picograms of Mercury (NOM)	45.4 pg
Primary Application	Speciality

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	14000.0
Mean Lumens (NOM)	10915.0
Nominal Initial Lumens per Watt (NOM)	65.11628
Color Temperature (NOM)	4100.0 K
Color Rendering Index (CRI) (NOM)	60.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	215.0
Open Circuit Voltage (instant start) Min @ Temperature	500 V @ 10 °C
Open Circuit Voltage (rapid start) Min @ Temperature	470 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	96.000 in(2438.4 mm)
Minimum Overall Length (NOM)	93.720 in(2380.5 mm)
Nominal Length (NOM)	96.000 in(2438.4 mm)
Bulb Diameter (DIA) (MIN)	2.000 in(50.8 mm)
Bulb Diameter (DIA) (MAX)	2.220 in(56.4 mm)
Bulb Diameter (DIA) (NOM)	2.125 in(54.0 mm)
End of Base Pin to End of Opposite Pin End (C) (NOM)	93.720 in(2380.5 mm)

PRODUCT INFORMATION

Product Code	11009
Description	F96PG17/CW
ANSI Code	1026-1
Standard Package	Case
Standard Package GTIN	10043168110096
Standard Package Quantity	8
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	8
UPC	043168110099