





GE
Lighting

29696 - CMH39T/U/942/G12

GE ConstantColor® CMH® Ceramic Metal Halide T4.5



CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

Caution

- Lamp may shatter and cause injury if broken
 - Do not use excessive force when installing lamp.
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
 - Do not exceed rated voltage.
 - Do not turn on lamp until fully installed.
 - Do not use beyond rated life.
 - Do not use lamp if outer glass is scratched or broken.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Operate lamp only in specified position.
 - Use in enclosed fixture rated for this product.
 - Use only properly rated ballast.
- A damaged lamp emits UV radiation which may cause eye/skin injury
 - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Burn
 - Allow lamp to cool before handling.
 - Do not turn on lamp until fully installed.
- Risk of Electric Shock
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Turn power off before inspection, installation or removal.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use fused or thermally protected ballast - see instructions.
 - Use in fixture rated for this product.

NOTES

- Rated life is 15,000 hours on magnetic ballasts.

GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - Ceramic Metal Halide
Bulb	T4.5
Base	Bi-Pin (G12)
Bulb Finish	Clear
Rated Life (NOM)	18000.0 h
Bulb Material	Quartz
Lamp Enclosure Type (LET)	Enclosed fixtures only
Base Temperature (MAX)	350.0 °C
Bulb Temperature (MAX)	500.0 °C
Mercury Content (NOM)	4.65 mg
Picograms of Mercury (NOM)	99.4 pg
Additional Info	UV control/Ballast thermal protection

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	3200.0
Mean Lumens (NOM)	2500.0
Nominal Initial Lumens per Watt (NOM)	82.05128
Color Temperature (NOM)	4200.0 K
Color Rendering Index (CRI) (NOM)	88.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	39.0
Burn Position	Universal burning position
Warm Up Time to 90% (MAX)	2.0 min
Hot Restart Time to 90% (MAX)	7.0 min

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	3.930 in(99.8 mm)
Bulb Diameter (DIA) (MAX)	0.570 in(14.5 mm)
Bulb Diameter (DIA) (NOM)	0.571 in(14.5 mm)
Light Center Length (LCL) (NOM)	2.200 in(55.9 mm)

PRODUCT INFORMATION

Product Code	29696
Description	CMH39T/U/942/G12
ANSI Code	C130/M130
Standard Package	Case
Standard Package GTIN	10043168296967
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168296960