

**Product** 64964**Number:****Order** MC70T6/U/G12/930**Abbreviation:**

General METALARC POWERBALL 70W ceramic metal halide tubular T6,
Description: clear, universal operation, G12 base, 3000K CCT, 95 CRI, pulse start, enclosed rated, 15,000 hour rated life

Product Information

Abbrev. With Packaging Info.	MC70T6UG12930 12/CS 1/SKU
Approx. Lumens (initial - horizontal)	6800
Approx. Lumens (initial - vertical)	6400
Approx. Lumens (mean - horizontal)	5120
Approx. Lumens (mean - vertical)	5120
Arc Length (in)	0.29
Arc Length (mm)	7.4
Base	G12
Bulb	T6
Color Rendering Index (CRI)	93
Color Temperature/CCT (K)	2950
Diameter (in)	0.748
Diameter (mm)	19.00
Family Brand Name	POWERBALL® CERAMIC METALARC® TUBULAR SINGLE-ENDED
Fixture Requirement	E
Hot Restrike Time (min)	2-15
Light Center Length - LCL (in)	2.2
Light Center Length - LCL (mm)	56
Maximum Base Temperature - Fahrenheit	536
Maximum Bulb Temperature - Fahrenheit	932
Maximum Overall Length - MOL (in)	3.94
Maximum Overall Length - MOL (mm)	100
Nominal Voltage (V)	88.00
Nominal Wattage (W)	70.00
Operating Position	Universal
Warm-up Time (min)	2-4

Footnotes

- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.