





GE  
Lighting

## 45178 - HSB160/M

GE Watt-Miser® E-Z Merc® Self-Ballasted ED24



### CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

#### Caution

- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use excessive force when installing lamp.
  - Do not use lamp if outer glass is scratched or broken.

#### Warning

- A damaged lamp emits UV radiation which may cause eye/skin injury
  - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Burn
  - Allow lamp to cool before handling.
  - Do not turn on lamp until fully installed.
- Unexpected lamp rupture may cause injury, fire, or property damage
  - Do not exceed rated voltage.
  - Do not use lamp if outer glass is scratched or broken.
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.
  - Use in enclosed fixture rated for this product.
- Risk of Electric Shock
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.
  - Keep combustible materials away from lamp.
  - Turn power off before inspection, installation or removal.
  - Use in fixture rated for this product.

### NOTES

- do not use this lamp in fixtures designed for less than rated lamp wattage

### GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - Self-Ballasted
Bulb	ED24
Base	Medium Screw (E26)
Bulb Finish	Coated
Rated Life (NOM)	12000.0 h
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Open or enclosed fixtures
Mercury Content (NOM)	2.5 mg
Picograms of Mercury (NOM)	23.1 pg

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2300.0
Mean Lumens (Vert)	9000.0
Mean Lumens (NOM)	1600.0
Nominal Initial Lumens per Watt (NOM)	14.375
Color Temperature (NOM)	3900.0 K
Color Rendering Index (CRI) (NOM)	50.0

### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	160.0
Voltage (NOM)	120.0
Burn Position	Universal burning position
Warm Up Time to 90% (MIN)	5.0 min
Warm Up Time to 90% (MAX)	7.0 min
Hot Restart Time to 90% (MIN)	3.0 min
Hot Restart Time to 90% (MAX)	6.0 min

### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	7.000 in(177.8 mm)
Nominal Length (NOM)	7.000 in(177.8 mm)
Bulb Diameter (DIA) (NOM)	3.000 in(76.2 mm)
Light Center Length (LCL) (NOM)	4.500 in(114.3 mm)

### PRODUCT INFORMATION

Product Code	45178
Description	HSB160/M
Standard Package	Case
Standard Package GTIN	10043168451786
Standard Package Quantity	24
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
UPC	043168451789