



Product 67517

Number:

Order LU150/55/D

Abbreviation:

General 150W LUMALUX high pressure sodium HID lamp, E39 based, ET23.5 bulb,
Description: universal burn, coated, 2100K

Product Information

Abbrev. With Packaging Info.	LU15055D 20/CS 1/SKU
ANSI Code	S55
Approx. Lumens (initial - horizontal)	14000
Approx. Lumens (initial - vertical)	14000
Approx. Lumens (mean - horizontal)	12500
Approx. Lumens (mean - vertical)	12500
Average Rated Life - Horizontal (hr)	30000
Average Rated Life - (hr)	30000
Avg Rated Life (hrs)	30000
Base	E39 Mogul
Bulb	ET23.5
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	2.937
Diameter (mm)	74.60
Family Brand Name	Lumalux®
Fixture Requirement	O
Hot Restrike Time (min)	1 MIN
Lamp Finish	Coated
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	7.75
Maximum Overall Length - MOL (mm)	197
Nominal Voltage (V)	55.00
Nominal Wattage (W)	150.00
Operating Position	Universal

Warm-up Time (min)

3-4 MINUTES

Footnotes

- Use with 4000V pulse rated sockets only.
- 55 Volt lamp.
- Mean lumens measured at 50% of average rated life
- LU150/100 and LU150/55 lamps are not interchangeable.