



Product Number: 67521

Order Abbreviation: LU250/D

General Description: 250W LUMALUX high pressure sodium HID lamp, E39 based, BT28 bulb, universal burn, coated, 2100K

Product Information

Abbrev. With Packaging Info.	LU250D 10/CS 1/SKU
ANSI Code	S50
Approx. Lumens (initial - horizontal)	26000
Approx. Lumens (initial - vertical)	26000
Approx. Lumens (mean - horizontal)	24400
Approx. Lumens (mean - vertical)	24400
Average Rated Life - Horizontal (hr)	30000
Average Rated Life - (hr)	30000
Avg Rated Life (hrs)	30000
Base	E39 Mogul
Bulb	BT28
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	3.543
Diameter (mm)	90.00
Family Brand Name	Lumalux®
Fixture Requirement	O
Hot Restrike Time (min)	1 MIN
Lamp Finish	Coated
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.98
Maximum Overall Length - MOL (mm)	228
Nominal Voltage (V)	100.00
Nominal Wattage (W)	250.00
Operating Position	Universal

Warm-up Time (min)

3-4 MINUTES

Footnotes

- Use with 4000V pulse rated sockets only.
- Mean lumens measured at 50% of average rated life