



Ceramalux ALTO

Ceramalux 200W Mog ED18 CL ALTO

These lamps pass the EPA's TCLP test for non-hazardous materials. Ideal for industrial applications, warehouses, post top applications and parking lots.

Product data

• General Characteristics

Base	Mogul [Mogul]
Base Information	Brass [Brass Base]
Bulb	ED18
Bulb Material	Hard Glass
Bulb Finish	Clear
Operating Position	Universal [Any or Universal (U)]
Main Application	General and Street Lighting
Rated Avg. Life	24000 hr

• Light Technical Characteristics

Color Rendering Index	21 Ra8
Color Temperature	2100 K
Color Temperature technical	2050 K
Initial Lumens	23000 Lm
Luminous Efficacy Lamp	115 Lm/W
Design Mean Lumens	19260 Lm
Chromaticity Coordinate X	521 -
Chromaticity Coordinate Y	420 -

• Electrical Characteristics

Watts	200 W
Lamp Voltage	100 V
Lamp Current	2.4 A
Ignition Time	5 (max) s
Re-ignition Time [min]	1 (max) min

• Environmental Characteristics

Mercury (Hg) Content	31 (max) mg
----------------------	-------------

• UV-related Characteristics

• Luminaire Design Requirements

Cap-Base Temperature	210 (max) C
Bulb Temperature	400 (max) C

• Product Dimensions



Light Center Length L	5.75 in
Max Overall Length (MOL) - C	9.75 (max) in
Diameter D	2.25 in

• Product Data

Product number	368779
Full product name	Ceramalux 200W Mog ED18 CL ALTO
Short product name	Ceramalx 200W Mog ED18 CL ALTO
Pieces per Sku	1
eop_pck_cfg	12
Skus/Case	12
Bar code on pack	46677368777
Bar code on case	50046677368772
Logistics code(s)	928601139501
eop_net_weight_pp	0.001 kg

PHILIPS

Dimensional drawing



E39

Ceramalux 200W Mog ED18 CL ALTO



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, February 1
data subject to change