



GE
Lighting

85381 - LU250/D/H/ECO

GE Ecolux® Lucalox® High Pressure Sodium ED28

Photo
Not Available



GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - High Pressure Sodium
Bulb	ED28
Base	Mogul Screw (E39)
Bulb Finish	Diffuse
Rated Life (NOM)	24000.0 h
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Open or enclosed fixtures
Base Temperature (MAX)	210.0 °C
Mercury Content (NOM)	16.4 mg
Picograms of Mercury (NOM)	29.2 pg
Additional Info	TCLP compliant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	26000.0
Mean Lumens (NOM)	23400.0
Nominal Initial Lumens per Watt (NOM)	104.0
Color Temperature (NOM)	2100.0 K
Color Rendering Index (CRI) (NOM)	22.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	250.0
Burn Position	Universal burning position
Warm Up Time to 90% (NOM)	3.0 min
Hot Restart Time to 90% (NOM)	1.0 min

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	9.000 in(228.6 mm)
Bulb Diameter (DIA) (MAX)	3.500 in(88.9 mm)
Light Center Length (LCL) (NOM)	5.000 in(127.0 mm)

PRODUCT INFORMATION

Product Code	85381
Description	LU250/D/H/ECO
ANSI Code	S50
Standard Package	Case
Standard Package GTIN	10043168853818
Standard Package Quantity	12
Sales Unit	Case
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168853811