



GE  
Lighting

## 20852 - 300PAR56/MFL

GE PAR56 - Medium Flood

Photo  
Not Available

Photo  
Not Available



### CAUTIONS & WARNINGS

#### Warning

- Risk of Fire
  - Keep combustible materials away from lamp.
- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
  - Use in enclosed fixture rated for this product.
  - Avoid direct water/liquid contact.

### NOTES

- For use with heat-resistant connector supported by bulb rim or metal shell of base.
- Lamp is made of heat resistant glass (HRG).

### GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR56
Base	Extended Mogul End Prong (GX16d EXT)
Filament	CC-13
Rated Life (NOM)	2000.0 h
Primary Application	Medium Flood

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	3450.0
Center Beam Candlepower (CBCP) (NOM)	30000.0
Nominal Initial Lumens per Watt (NOM)	11.5

### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	300.0
Voltage (NOM)	230.0

### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.000 in(127.0 mm)
Bulb Diameter (DIA) (NOM)	7.000 in(177.8 mm)

### PRODUCT INFORMATION

Product Code	20852
Description	300PAR56/MFL
Standard Package	Case
Standard Package GTIN	10043168208526
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168208529