


19878 - 50PAR36/H/SP5

GE PAR36 - Very Narrow Spot

Standard Halogen - Crisp, white light







CAUTIONS & WARNINGS

Caution

- · Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp/fixture to cool before handling.
- A damaged lamp emits UV radiation which may cause eye/skin injury
- Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not exceed 110% of rated voltage.
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in fixture rated for this product.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Rated Life (NOM) Primary Application Sealed Beam - PAR PAR36 Screw Terminals C-6 4000.0 h Very Narrow Spot

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)400Beam Spread (NOM)5.0Beam Spread - Horizontal6.0Beam Spread - Vertical4.0Center Beam Candlepower390(CBCP) (NOM)Color Temperature (NOM)Color Temperature (NOM)305Max. Beam Candlepower390(MBCP) (MAX)Nominal Initial Lumens per Watt8.0(NOM)

400.0 5.0 ° 6.0 - 10.0 ° 4.0 - 10.0 ° 39000.0 3050.0 K 39000.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	50.0
Voltage (NOM)	12.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM) 2.750 in(69.8 mm) 4.500 in(114.3 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168970242