





GE
Lighting

19023 - 120 PAR 56 VNSP

GE PAR56 - Very Narrow Spot



CAUTIONS & WARNINGS

Warning

- Risk of Fire
 - Keep combustible materials away from lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
 - Use in enclosed fixture rated for this product.
 - Avoid direct water/liquid contact.

NOTES

- For use with heat-resistant connector supported by bulb rim or metal shell of base.
- Lamp is made of heat resistant glass (HRG).

GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR56
Base	Screw Terminals
Filament	C-6
Rated Life (NOM)	2000.0 h
Primary Application	Very Narrow Spot

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1050.0
Beam Spread - Horizontal	15.0 - 10.0 °/8.0 - 50.0 °
Beam Spread - Vertical	10.0 - 10.0 °/6.0 - 50.0 °
Center Beam Candlepower (CBCP) (NOM)	60000.0
Color Temperature (NOM)	2750.0 K
Nominal Initial Lumens per Watt (NOM)	8.75

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	120.0
Voltage (NOM)	12.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	4.500 in(114.3 mm)
Bulb Diameter (DIA) (NOM)	7.000 in(177.8 mm)

PRODUCT INFORMATION

Product Code	19023
Description	120 PAR 56 VNSP
Standard Package	Case
Standard Package GTIN	10043168190234
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168190237