






GE
Lighting

14689 - 886/BP

GE T3.25 (T3 1/4) - Automotive



CAUTIONS & WARNINGS

Caution

- Risk of Burn
 - Allow lamp/fixture to cool before handling.

Warning

- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Avoid direct water/liquid contact.
 - Dispose of lamp in a closed container.
 - Do not exceed rated voltage.
 - Do not turn on lamp until fully installed.
 - Do not use lamp if outer glass is scratched or broken.
 - Keep children away.
 - Use eye protection when handling lamp.
 - Use in enclosed fixture rated for this product.
 - Use protective screen when handling.

GENERAL CHARACTERISTICS

| | |
|---------------------|------------------------------|
| Lamp Type | Miniature - T & TL Shape |
| Bulb | T3.25 (T3 1/4) |
| Base | Right Angle Prefocus (PGJ13) |
| Filament | C-6 |
| Rated Life (NOM) | 200.0 h |
| Bulb Material | Hard glass |
| Atmosphere | Gas-filled |
| Primary Application | Fog/Driving |

PHOTOMETRIC CHARACTERISTICS

| | |
|---|--------|
| Initial Lumens (NOM) | 1257.0 |
| Nominal Initial Lumens per Watt (NOM) | 25.14 |
| Mean Spherical Candlepower (MSCP) (NOM) | 100.0 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|------|
| Wattage (NOM) | 50.0 |
| Voltage (NOM) | 12.8 |

DIMENSIONS

| | |
|------------------------------------|-------------------|
| Maximum Overall Length (MOL) (NOM) | 2.680 in(68.1 mm) |
| Bulb Diameter (DIA) (NOM) | 0.406 in(10.3 mm) |
| Light Center Length (LCL) (NOM) | 1.250 in(31.8 mm) |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 14689 |
| Description | 886/BP |
| ANSI Code | 886 |
| Standard Package | Master |
| Standard Package GTIN | 50043168146895 |
| Standard Package Quantity | 48 |
| Sales Unit | Blister |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 48 |
| UPC | 043168146890 |