

19566 - 2586

GE T4 - Aircraft; Low Voltage



CAUTIONS & WARNINGS

Caution

- Risk of Burn
- Allow lamp/fixture to cool before handling.

- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.
- · Risk of Fire
- Keep combustible materials away from lamp.
- Use in fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not touch glass with bare hands.
- Do not turn on lamp until fully installed.
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use protective screen when handling.

GENERAL CHARACTERISTICS

Lamp Type Miniature - T & TL Shape

Bulb

2-Pin with Insulation Leads Base

Filament CC-6 Rated Life (NOM) 100.0 h **Bulb Material** Quartz Atmosphere Gas-filled

Primary Application Aircraft;Low Voltage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 7540.0 Nominal Initial Lumens per Watt 30.16

(NOM)

Mean Spherical Candlepower

(MSCP) (NOM)

600.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 250.0 Voltage (NOM) 28.0

DIMENSIONS

Maximum Overall Length 1.900 in(48.3 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 0.500 in(12.7 mm) Light Center Length (LCL) 1.300 in(33.0 mm)

(NOM)

PRODUCT INFORMATION

Product Code 19566 Description 2586 ANSI Code 2586 Standard Package Case

Standard Package GTIN 10043168195666

Standard Package Quantity 100 Sales Unit Bulk No Of Items Per Sales Unit 1 No Of Items Per Standard 100

Package

UPC 043168195669