

# 25149 - 9004NH/BP

GE NIGHTHAWK™ T4.75 (T4 3/4) - Automotive



### **CAUTIONS & WARNINGS**

#### Warning

- Risk of Burn
- Allow lamp/fixture to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Avoid direct water/liquid contact.
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not turn on lamp until fully installed.
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Use protective screen when handling.

## **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament Rated Life (NOM) Bulb Material Atmosphere Primary Application Miniature - T & TL Shape T4.75 (T4 3/4) Axial Plastic Prefocus C-6/C-6 150.0/320.0 h Hard glass Gas-filled Headlamp-Low beam only;Headlamp-High/Low beam;Headlamp-High beam only

### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) Nominal Initial Lumens per Watt (NOM) Mean Spherical Candlepower (MSCP) (NOM)

1195.0 /690.0 18.38462 /15.33333

95.0 /55.0

# ELECTRICAL CHARACTERISTICS

Wattage (NOM) Voltage (NOM) 65.0 12.8

12.8

## DIMENSIONS

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM) Light Center Length (LCL) (NOM) 4.170 in(105.9 mm) 0.594 in(15.1 mm) 1.750 in(44.4 mm)

## **PRODUCT INFORMATION**

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

May 27, 2014 5:43:12 PM For additional information, visit www.gelighting.com