



GE
Lighting

27688 - 1816

GE T3.25 (T3 1/4) - Automotive; Low Voltage

Photo
Not Available



GENERAL CHARACTERISTICS

Lamp Type	Miniature - T & TL Shape
Bulb	T3.25 (T3 1/4)
Base	Miniature Bayonet (Ba9s)
Filament	C-2V
Rated Life (NOM)	1000.0 h
Atmosphere	Vacuum
Primary Application	Low Voltage;Ash tray;Auto Transmission Indicator;Brake Warning;Clock;Directional Signal Indicator;Dome;Glove Box;Hi-Beam Indicator;Ignition Switch;Instrument, General;License Plate;Map;Radio dial;Seat Belt Warning;Sidemarker, Front;Sidemarker, Rear;Step/Courtesy;Under Hood

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	38.0
Nominal Initial Lumens per Watt (NOM)	9.5
Mean Spherical Candlepower (MSCP) (NOM)	3.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	4.0
Voltage (NOM)	13.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	1.190 in(30.2 mm)
Bulb Diameter (DIA) (NOM)	0.406 in(10.3 mm)
Light Center Length (LCL) (NOM)	0.620 in(15.7 mm)

PRODUCT INFORMATION

Product Code	27688
Description	1816
ANSI Code	1816
Standard Package	Case
Standard Package GTIN	20043168276881
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168276887