



GE  
Lighting

### 39641 - 1962B

GE Quartzline® T3 - Low Voltage

Photo  
Not Available



#### CAUTIONS & WARNINGS

##### Caution

- Risk of Burn
  - Allow lamp/fixture to cool before handling.

##### Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
  - Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
  - Dispose of lamp in a closed container.
  - Do not exceed rated voltage.
  - Do not touch glass with bare hands.
  - Do not turn on lamp until fully installed.
  - Do not use lamp if outer glass is scratched or broken.
  - Keep children away.
  - Use eye protection when handling lamp.
  - Use protective screen when handling.

#### GENERAL CHARACTERISTICS

Lamp Type	Miniature - T & TL Shape
Bulb	T3
Base	Wire Terminals
Filament	C-6
Rated Life (NOM)	50.0 h
Bulb Material	Quartz
Atmosphere	Gas-filled
Primary Application	Low Voltage

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1382.0
Nominal Initial Lumens per Watt (NOM)	22.29032
Mean Spherical Candlepower (MSCP) (NOM)	110.0

#### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	62.0
Voltage (NOM)	8.5

#### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	1.140 in(29.0 mm)
Bulb Diameter (DIA) (NOM)	0.375 in(9.5 mm)
Light Center Length (LCL) (NOM)	0.285 in(7.2 mm)

#### PRODUCT INFORMATION

Product Code	39641
Description	1962B
ANSI Code	1962B
Standard Package	Case
Standard Package GTIN	20043168396411
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard	10
Package	
UPC	043168396417