



GE
Lighting

41938 - 1970X

GE Quartzline® T3 - Aircraft; Low Voltage

Photo
Not Available



CAUTIONS & WARNINGS

Caution

- Risk of Burn
 - Allow lamp/fixture to cool before handling.

Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
 - Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Dispose of lamp in a closed container.
 - Do not exceed rated voltage.
 - Do not touch glass with bare hands.
 - Do not turn on lamp until fully installed.
 - Do not use lamp if outer glass is scratched or broken.
 - Keep children away.
 - Use eye protection when handling lamp.
 - Use protective screen when handling.

NOTES

- Filament supported.

GENERAL CHARACTERISTICS

Lamp Type	Miniature - T & TL Shape
Bulb	T3
Base	Special Sleeve
Filament	CC-8
Rated Life (NOM)	1000.0 h
Atmosphere	Gas-filled
Primary Application	Aircraft;Low Voltage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1759.0
Nominal Initial Lumens per Watt (NOM)	17.59
Mean Spherical Candlepower (MSCP) (NOM)	140.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	100.0
Voltage (NOM)	28.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	2.250 in(57.2 mm)
Bulb Diameter (DIA) (NOM)	0.375 in(9.5 mm)

PRODUCT INFORMATION

Product Code	41938
Description	1970X
ANSI Code	1970X
Standard Package	Case
Standard Package GTIN	20043168419387
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168419383