



Product Number: 54070

Order Abbreviation: HMI 2500W/SE/XS

General Description: 2,500 watt, metal halide, single-ended, 6000K

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	HMI2500WSEX5 115V 1/CS 1/SKU
Application	Film, TV & Video Production. Studio Ltg
Average Rated Life (hr)	500
Base	G38 Mogul Bipost
Bulb	GST60
Class	C (gas)
Color Rendering Index (CRI)	90
Color Temperature (K)	6000
Cooling	Convection
Current (A)	25.6
Diameter d (in)	2.362
Diameter d (mm)	60.00
Distance a (mm)	127
Electrode Gap (cold) (mm)	14
Family Brand Name	HMI®
Hot Restart	Yes
Lamp Finish	Clear
Length l (mm)	225
Length l max. (mm)	225
Light Center Length - LCL (mm)	127
Luminous Efficacy (lm/W)	96
Luminous Flux (lm)	240000
Maximum Base Temperature °C	450
Maximum Overall Length - MOL (mm)	225
Nominal Voltage (V)	115.00
Nominal Wattage (W)	2500.00
Operating Position	Any
Type of Current	AC

Footnotes

- Type of current: sine-wave (sinusoidal) AC.
- Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.