



Product Number: 54288

Order Abbreviation: HSD 250W/UL/75 4ARXS

General Description: 250 watt, metal halide, single-ended, with outer jacket, not hot restart, 4ARXS HSD lamp series

Product Information

Abbrev. With Packaging Info.	HSD 250WUL75 4ARXS 10/CS 1/SKU
Application	Entertainment, Effect and Architectural Lighting
Average Rated Life (hr)	6000
Base	GY9.5 BIPIN
Bulb	MAX 23MM
Class	C (gas)
Color Rendering Index (CRI)	85
Color Temperature (K)	7500
Cooling	Convection
Current (A)	3.1
Diameter d (in)	0.906
Diameter d (mm)	23.00
Distance a (mm)	55
Electrode Gap (cold) (mm)	5
Family Brand Name	4ArXS HSD®
Hot Restart	No
Lamp Finish	Clear
Length l (mm)	108
Length l max. (mm)	108
Light Center Length - LCL (mm)	55
Luminous Flux (lm)	15000
Maximum Base Temperature °C	450
Maximum Overall Length - MOL (mm)	108
Nominal Voltage (V)	85.00
Nominal Wattage (W)	250.00
Operating Position	Any
Reflector Coating	23.00
Type of Current	AC



Footnotes

- Type of current: sine-wave (sinusoidal) AC.
- Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.