



GE
Lighting

41629 - 75PAR16/H/FL30

GE energy-efficient halogen 75 watt PAR16 floodlight 1-pack

- GE energy-efficient halogen bulbs deliver crisp, white light. This unsurpassed light quality is ideal for adding depth, drama and interest to any room. These GE energy-efficient halogen floodlights use less energy than standard halogen bulbs, saving money on energy. GE energy-efficient halogen floodlights feature lenses designed to provide a precise beam pattern, dispensing broad beams of crisp, white light throughout your home's interior. Use these bulbs in indoor track and recessed fixtures instead of regular incandescent and create a dramatic effect
- Edison™ halogen bulbs provide a brighter, crisper light that makes your home look its best
- That's why professionals choose Edison for exceptional results and longer bulb life.
- Showcase the beauty of your home with the highest quality of light.
- Estimated yearly energy costs \$9.03 based on 3 hours per day \$0.11 per kWh
- Lasts 1.8 years based on 3 hours per day usage
- PAR16 indoor floodlight with medium base for use in directional fixtures such as recessed can lighting



GENERAL CHARACTERISTICS

| | |
|---------------------|-------------------|
| Lamp Type | Halogen - PAR |
| Bulb | PAR16 |
| Base | Medium NP |
| Filament | CC-8 |
| Rated Life (NOM) | 2000.0 h |
| Primary Application | Indoor Floodlight |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------------|----------|
| Initial Lumens (NOM) | 900.0 |
| Center Beam Candlepower (CBCP) (NOM) | 1600.0 |
| Color Temperature (NOM) | 2950.0 K |
| Beam Spread (NOM) | 30.0 ° |
| Nominal Initial Lumens per Watt (NOM) | 12.0 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|----------------------------|
| Wattage (NOM) | 75.0 |
| Voltage (NOM) | 120.0 |
| Burn Position | Universal burning position |

DIMENSIONS

| | |
|------------------------------------|-------------------|
| Maximum Overall Length (MOL) (NOM) | 2.875 in(73.0 mm) |
| Bulb Diameter (DIA) (NOM) | 2.000 in(50.8 mm) |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 41629 |
| Description | 75PAR16/H/FL30 |
| Standard Package | Case |
| Standard Package GTIN | 10043168416297 |
| Standard Package Quantity | 6 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 6 |
| UPC | 043168416290 |



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
 - Allow lamp to cool before handling.
- Risk of Fire
 - Keep combustible materials away from lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Do not use lamp if outer glass is scratched or broken.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.