

# 11116 - 50PAR30L/H/FL40

## GE energy-efficient halogen 50 watt PAR30 longneck floodlight 1-pack

- GE energy-efficient halogen bulbs deliver crisp, white light. This unsurpassed light quality is ideal for adding depth, drama and interest to any room. These GE energy-efficient halogen floodlights use less energy than standard halogen bulbs, saving money on energy. GE energy-efficient halogen floodlights feature lenses designed to provide a precise beam pattern, dispensing broad beams of crisp, white light throughout your home's interior. Use these bulbs in indoor track and recessed fixtures instead of regular incandescent and create a dramatic effect
- Edison™ halogen bulbs provide a brighter, crisper light that makes your home look its best
- That's why professionals choose Edison for exceptional results and longer bulb life.
- Showcase the beauty of your home with the highest quality of light.
- Estimated yearly energy costs \$6.02 based on 3 hours per day \$0.11 per kWh
- Lasts 2.7 years based on 3 hours per day usage
- PAR30 longneck indoor floodlight with medium base for use in directional fixtures such as recessed can lighting

#### **Energy Savings**











## **CAUTIONS & WARNINGS**

### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

### Warning

- Risk of Burn
- Allow lamp to cool before handling.
- Risk of Fire
  - Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Do not use where directly exposed to water or outdoors without an enclosed fixture.
- \*Two year life based on rated life at 4 hours/day

# **GENERAL CHARACTERISTICS**

Lamp Type Halogen - PAR
Bulb PAR30L
Base Medium NP
Filament CC-8
Rated Life (NOM) 3000.0 h
Primary Application Indoor Floodlight

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 580.0 Center Beam Candlepower 1100.0

(CBCP) (NOM)

Color Temperature (NOM) 2800.0 K Beam Spread (NOM) 40.0 ° Nominal Initial Lumens per Watt (NOM) 11.6

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 50.0 Voltage (NOM) 120.0

Burn Position Universal burning position

### **DIMENSIONS**

Maximum Overall Length 4.750 in(120.6 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 3.750 in(95.2 mm)

#### PRODUCT INFORMATION

Product Code 11116

Description 50PAR30L/H/FL40

Standard Package Case

Standard Package GTIN 10043168111161

Standard Package Quantity

Sales Unit

No Of Items Per Sales Unit

No Of Items Per Standard

15

Package

UPC 043168111164