



GE
Lighting

14748 - 75PAR/H/FL25-6PK

GE Floodlight PAR38

- Designed with a unique all-weather construction, they withstand harsh weather conditions better than regular bulbs.
- Uses Halogen technology for a brighter, crisper light
- Lasts 25% longer than regular bulbs*
- GE's Floodlights cast a wider beam that adds drama to driveways and yards.



GENERAL CHARACTERISTICS

Lamp Type	Halogen - PAR
Bulb	PAR38
Base	Medium Skirt (E26/50x39)
Filament	CC-8
Rated Life (NOM)	2500.0 h
Primary Application	Yard Stake; Indoor and outdoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1050.0
Center Beam Candlepower (CBCP) (NOM)	4000.0
Color Temperature (NOM)	2850.0 K
Beam Spread (NOM)	25.0 °
Nominal Initial Lumens per Watt (NOM)	14.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	75.0
Voltage (NOM)	120.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.313 in(135.0 mm)
Bulb Diameter (DIA) (NOM)	4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code	14748
Description	75PAR/H/FL25-6PK
Standard Package	Case
Standard Package GTIN	10043168147481
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168147484

CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
 - Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
 - Keep combustible materials away from lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.

*20 month life based on rated life at 4 hours/day.