


16393 - 75PAR30L/H/WFL

GE energy-efficient halogen 75 watt PAR30 longneck floodlight 1-pack

- GE energy-efficient halogen bulbs deliver crisp, white light. This unsurpassed light quality is ideal for adding depth, drama and interest to any room. These GE energy-efficient halogen floodlights use less energy than standard halogen bulbs, saving money on energy. GE energy-efficient halogen floodlights feature lenses designed to provide a precise beam pattern, dispensing broad beams of crisp, white light throughout your home's interior. Use these bulbs in indoor track and recessed fixtures instead of regular incandescent and create a dramatic effect
- Edison™ halogen bulbs provide a brighter, crisper light that makes your home look its best
- That's why professionals choose Edison for exceptional results and longer bulb life.
- Showcase the beauty of your home with the highest quality of light.
- Estimated yearly energy costs \$9.03 based on 3 hours per day \$0.11 per kWh
- Lasts 2.7 years based on 3 hours per day usage
- PAR30 longneck indoor floodlight with medium base for use in directional fixtures such as recessed can lighting

Energy Savings











CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp to cool before handling
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Do not use where directly exposed to water or outdoors without an enclosed fixture.
- *Two year life based on rated life at 4 hours/day

GENERAL CHARACTERISTICS

Lamp Type Halogen - PAR
Bulb PAR30L
Base Medium NP
Filament CC-8
Rated Life (NOM) 3000.0 h
Primary Application Indoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1050.0 Center Beam Candlepower 620.0

(CBCP) (NOM)

Color Temperature (NOM) 2830.0 K Beam Spread (NOM) 30.0 ° Nominal Initial Lumens per Watt 14.0

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 75.0 Voltage (NOM) 120.0

Burn Position Universal burning position

DIMENSIONS

Maximum Overall Length 4.750 in(120.6 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 3.750 in(95.2 mm)

PRODUCT INFORMATION

Product Code 16393

Description 75PAR30L/H/WFL

Standard Package Case

Standard Package GTIN 00043168163934

Standard Package Quantity 6
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 6

Package

UPC 043168111539