


27218 - 80PAR/HIR/FL25

GE HIR™ PAR38


- Up to 20% longer life -3000 hours
- Up to 28% more efficient than standard halogen Up to 22% energy savings

a product of

ecomagination-









CAUTIONS & WARNINGS

Caution

- · Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage - Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Rated Life (NOM) **Primary Application** Halogen - PAR PAR38 Medium Skirt (E26/50x39) CC-8 3000.0 h Indoor and outdoor Floodlight

PHOTOMETRIC CHARACTERISTICS 1500.0

Initial Lumens (NOM) Center Beam Candlepower 5000.0 (CBCP) (NOM) Color Temperature (NOM) 2900.0 K Beam Spread (NOM) 25.0 ° Nominal Initial Lumens per Watt (NOM)

18.75

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	80.0
Voltage (NOM)	120.0

DIMENSIONS

Maximum Overall Length	5.313 in(135.0 mm)
(MOL) (NOM)	
Bulb Diameter (DIA) (NOM)	4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168272186