



GE
Lighting

41547 - 45PAR30HIR/FL25X

GE Compact HIR™ HIR XL® PAR30

a product of
ecomagination

Energy Savings

Photo
Not Available

Photo
Not Available



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
 - Allow lamp to cool before handling.
- Risk of Fire
 - Keep combustible materials away from lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Do not use lamp if outer glass is scratched or broken.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.

GENERAL CHARACTERISTICS

Lamp Type	Halogen - PAR
Bulb	PAR30
Base	Medium NP
Filament	CC-8
Rated Life (NOM)	6000.0 h
Bulb Material	Sodalime glass

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	620.0
Center Beam Candlepower (CBCP) (NOM)	2025.0
Color Temperature (NOM)	2680.0 K
Beam Spread (NOM)	25.0 °
Nominal Initial Lumens per Watt (NOM)	13.77778

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	45.0
Voltage (NOM)	120.0
Burn Position	Universal

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	3.620 in(91.9 mm)
Bulb Diameter (DIA) (NOM)	3.750 in(95.2 mm)

PRODUCT INFORMATION

Product Code	41547
Description	45PAR30HIR/FL25X
Standard Package	Case
Standard Package GTIN	10043168415474
Standard Package Quantity	15
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	15
UPC	043168415477