

### 14876 - FCR

GE Quartzline® T3 - Equipment; Overhead Projection





#### **CAUTIONS & WARNINGS**

#### Caution

- Risk of Burn
- Allow lamp/fixture to cool before handling.
- Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Avoid direct water, liquid or metal contact.
- Do not exceed 110% of rated voltage.
- Do not use lamp if outer glass is scratched or broken.

- Use in enclosed fixture rated for this product.

#### **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament Rated Life (NOM) Primary Application Halogen - Single-Ended T3 2-Pin (GY6.35) C-6 Oval 50.0 h Equipment;Overhead Projection

Horizontal ±15° or Base

#### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) Color Temperature (NOM) Source Size (W) x (H) Nominal Initial Lumens per Watt (NOM)

2800.0 3300.0 K 0.2 x 0.15 in 28.0

12.0

Down

#### **ELECTRICAL CHARACTERISTICS**

## Wattage (NOM) 100.0

# DIMENSIONS

Voltage (NOM)

Burn Position

Maximum Overall Length<br/>(MOL) (NOM)1.750 in(44.4 mm)Bulb Diameter (DIA) (NOM)0.375 in(9.5 mm)Light Center Length (LCL)1.180 in(30.0 mm)(NOM)0.375 in(9.5 mm)

#### **PRODUCT INFORMATION**

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 14876 FCR FCR Case 10043168148761 100 Unit 1 100

043168148764