


GE MR16





CAUTIONS & WARNINGS

Caution

- · Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp/fixture to cool before handling.
- Turn power off before installing lamp.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product-- see instructions.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.

GENERAL CHARACTERISTICS

Lamp Type	Halogen - MR
Bulb	MR16
Base	2-Pin (GX5.3)
Filament	C-6
Rated Life (NOM)	2000.0 h

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	275.0
Center Beam Candlepower	500.0
(CBCP) (NOM)	
Color Temperature (NOM)	2900.0 K

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	20.0
Voltage (NOM)	12.0

DIMENSIONS

Maximum Overall Length	1.875 in(47.6 mm)
(MOL) (NOM)	
Bulb Diameter (DIA) (NOM)	2.000 in(50.8 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 25480 Q20MR16/FL BAB BUNDLE 30043168254800 20 Unit 1 20

043168254809