

# 29604 - BRH

GE Quartzline® T5 - Stage & Studio; Double Ended; Overhead Projection This product is no longer manufactured.

# 



## **CAUTIONS & WARNINGS**

#### Caution

- Risk of Burn
- Allow lamp/fixture to cool before handling.
- Turn power off before installing lamp.
- · Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Avoid direct water, liquid or metal contact.
- Do not exceed 110% of rated voltage.
- Do not use lamp if outer glass is scratched or broken.
- Use in enclosed fixture rated for this product.

#### **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base

Filament Rated Life (NOM) Primary Application Halogen - Double-Ended T5 Recessed Single Contact (R7s) CC-8 60.0 h Stage & Studio;Double Ended;Overhead Projection

## **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) Color Temperature (NOM) Source Size (W) x (H) Nominal Initial Lumens per Watt (NOM)

30000.0 3350.0 K 0.7 x 0.21 in 30.0

### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)1000.0Voltage (NOM)120.0Burn PositionUniversal burning position

### DIMENSIONS

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM) Light Center Length (LCL) (NOM)

3.750 in(95.2 mm) 0.625 in(15.9 mm) 0.750 in(19.0 mm)

#### PRODUCT INFORMATION Product Code

Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 29604 BRH BRH Case 10043168296042 24 Unit 1 24

043168296045