




GE  
Lighting

### 35321 - FDT

GE Quartzline® T3 - Equipment; Overhead Projection



#### CAUTIONS & WARNINGS

##### Caution

- Risk of Burn
  - Allow lamp/fixture to cool before handling.
  - Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use lamp if outer glass is scratched or broken.

##### Warning

- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
  - Avoid direct water, liquid or metal contact.
  - Do not exceed 110% of rated voltage.
  - Do not use lamp if outer glass is scratched or broken.
  - Use in enclosed fixture rated for this product.

#### GENERAL CHARACTERISTICS

Lamp Type	Halogen - Single-Ended
Bulb	T3
Base	Oriented Medium 2-Pin (GZ9.5)
Filament	C-6 Oval
Rated Life (NOM)	50.0 h
Primary Application	Equipment;Overhead Projection

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2900.0
Color Temperature (NOM)	3300.0 K
Source Size (W) x (H)	0.23 x 0.15 in
Nominal Initial Lumens per Watt (NOM)	29.0

#### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	100.0
Voltage (NOM)	12.0
Burn Position	Horizontal $\pm 15^\circ$ or Base Down

#### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	2.120 in(53.8 mm)
Bulb Diameter (DIA) (NOM)	0.375 in(9.5 mm)
Light Center Length (LCL) (NOM)	1.060 in(26.9 mm)

#### PRODUCT INFORMATION

Product Code	35321
Description	FDT
ANSI Code	FDT
Standard Package	Case
Standard Package GTIN	10043168353219
Standard Package Quantity	24
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
UPC	043168353212