





## **CAUTIONS & WARNINGS**

## Caution

- Risk of Burn
- Allow lamp to cool before handling.
- Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Do not exceed 110% of rated voltage.

## **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament

**Bulb Finish** 

Rated Life (NOM)

Halogen - Single-Ended T4 Double Contact Bayonet (BA15d) CC-2V Clear 1000.0 h

# **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM)2800.0Color Temperature (NOM)2950.0 KNominal Initial Lumens per Watt18.66667(NOM)19.000 (NOM)

**ELECTRICAL CHARACTERISTICS** 

Wattage (NOM)	150.0
Voltage (NOM)	120.0

# DIMENSIONS

 
 Maximum Overall Length (MOL) (NOM)
 2.438 in(61.9 mm)

 Bulb Diameter (DIA) (NOM)
 0.500 in(12.7 mm)

 Light Center Length (LCL)
 1.375 in(34.9 mm)

 (NOM)
 1.375 in(34.9 mm)

**PRODUCT INFORMATION** 

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 44384 Q150CL/DC/2V ESP Case 10043168443842 6 Unit 1 6

043168443845