


GE T4





### **CAUTIONS & WARNINGS**

#### Caution

- Risk of Burn
- Allow lamp to cool before handling.
- Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Do not exceed 110% of rated voltage.

# **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament Bulb Finish

Rated Life (NOM)

Halogen - Single-Ended T4 Double Contact Bayonet (BA15d) CC-2V Clear 750.0 h

# **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM)1800.0Color Temperature (NOM)2950.0 KNominal Initial Lumens per Watt18.0(NOM)18.0

# **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)	100.0
Voltage (NOM)	120.0

# DIMENSIONS

Maximum Overall Length	2.438 in(61.9 mm)
(MOL) (NOM)	
Bulb Diameter (DIA) (NOM)	0.500 in(12.7 mm)
Light Center Length (LCL)	1.375 in(34.9 mm)
(NOM)	

# **PRODUCT INFORMATION**

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 44386 Q100CL/DC/2V ESR Case 10043168443866 6 Unit 1 6

043168443869