



Product Number: 54259

Order Abbreviation: EVD 64663 HLX

General Description: 400 watt, tungsten halogen, low volt without reflector

Product Information

Abbrev. With Packaging Info.	EVD64663HLX 36V 40/CS 1/SKU
Application	Projector, Microfilm, Studio
Average Rated Life (hr)	50
Base	G6.35 Bipin
Bulb	R111
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3250
Diameter d (in)	0.630
Diameter d (mm)	16.00
Distance a (in)	1.404
Distance a (mm)	36
Family Brand Name	XENOPHOT® (HLX)
Filament	C-Bar-6
Filament Dimensions Length (in)	0.191
Filament Dimensions Length (mm)	10
Filament Dimensions Width (in)	.362
Filament Dimensions Width (mm)	9.3
Lamp Finish	Clear
Length l (in)	2.34
Length l (mm)	60
Length l max. (in)	2.34
Length l max. (mm)	60
LIF Code	A1/239
Light Center Length - LCL (in)	1.404
Light Center Length - LCL (mm)	36
Luminous Flux (lm)	16200
Maximum Overall Length - MOL (in)	2.34
Maximum Overall Length - MOL (mm)	60
Nominal Voltage (V)	36.00
Nominal Wattage (W)	400.00

Operating Position	s 90
Reflector Coating	16.00
Type of Current	AC

Footnotes

- s (Operating Position) = Vertical, base down