



Product Number: 54276

Order Abbreviation: FDT 64628

General Description: 100 WATT, TUNGSTEN HELOGEN, LOW VOLTAGE WITHOUT REFLECTOR

Product Information

Abbrev. With Packaging Info.	FDT64628 12V 12/CS 1/SKU
ANSI Code	FDT
Application	Projector, Stage & Studio
Average Rated Life (hr)	50
Base	GY9.5 BIPIN
Bulb	T11,5
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3500
Diameter d (in)	0.472
Diameter d (mm)	12.00
Distance a (in)	1.053
Distance a (mm)	27
Filament Dimensions Length (in)	0.090
Filament Dimensions Length (mm)	2.3
Filament Dimensions Width (in)	0.164
Filament Dimensions Width (mm)	4.2
Lamp Finish	Clear
Length l (in)	2.223
Length l (mm)	57
LIF Code	A1/261
Light Center Length - LCL (in)	1.053
Light Center Length - LCL (mm)	27
Luminous Flux (lm)	3420
Maximum Overall Length - MOL (in)	2.223
Maximum Overall Length - MOL (mm)	57
Nominal Voltage (V)	12.00
Nominal Wattage (W)	100.00

Operating Position	s 90
Reflector Coating	12.00
Type of Current	AC

Footnotes

- s (Operating Position) = Vertical, base down