



Product 54631

Number:

Order FRK

Abbreviation:

General 650 watt, tungsten halogen, medium to high voltage, single-ended
Description:

Product Information

Abbrev. With Packaging Info.	FRK 120V 24/CS 1/SKU
ANSI Code	FRK
Application	Stage & Studio
Average Rated Life (hr)	200
Base	GY9.5 BIPIN
Bulb	T7
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3200
Diameter d (in)	0.748
Diameter d (mm)	19.00
Distance a (in)	1.831
Distance a (mm)	46.5
Filament	C-13D
Filament Dimensions Length (in)	0.728
Filament Dimensions Length (mm)	18.5
Filament Dimensions Width (in)	0.63
Filament Dimensions Width (mm)	16
Lamp Finish	Clear
Length l (in)	3.510
Length l (mm)	90
Length l max. (in)	3.510
Length l max. (mm)	90
LIF Code	CP/89
Light Center Length - LCL (in)	1.831
Light Center Length - LCL (mm)	46.5
Luminous Flux (lm)	16900
Maximum Overall Length - MOL (in)	3.510
Maximum Overall Length - MOL (mm)	90
Nominal Voltage (V)	120.00
Nominal Wattage (W)	650.00

Operating Position

s 90

Type of Current

AC

Footnotes

- s (Operating Position) = Vertical, base down