

**Product** 58324**Number:****Order** 35MR16/FL35/C(FMW)12V**Abbreviation:****General** Tungsten Halogen Tru-Aim MR16 STANDARD Axial Filament**Description:** UV-Filter Dichroic Reflector Cover Glass GU5.3 Bi-Pin Base
35Watt 12Volt Flood Beam*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	35MR16FL35CFMW 12V 20/CS 1/SKU
ANSI Code	FMW
Average Rated Life (hr)	2000
Base	GU5.3 Bipin
Beam Angle (deg)	36
Beam Type	WFL
Bulb	MR16
Centerbeam Candlepower (cp)	1000
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	2900
Diameter (in)	2.008
Diameter (mm)	51.00
Ecologic	YES
Family Brand Name	TRU-AIM Standard
Filament	AXIAL
Horizontal Beam Angle (deg)	35
Lamp Finish	Covered
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	45.0
Nominal Voltage (V)	12.00
Nominal Wattage (W)	35.00
Vertical Beam Angle (deg)	35

**Footnotes**

- UV Filter capsul with axial filament in covered dichroic reflector.

- Max. seal temperature 370 C (662F)
- Max pin temperature 250 C.
- Max temperature at lens reflector joint 240 C.
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.