



30145 - DXC

GE R40 - Photofloods

• High color rendering (65-70CRI), much better than standard HPS This product is no longer manufactured. Remaining stock will be sold.







CAUTIONS & WARNINGS

Caution

Risk of Burn

- Allow lamp/fixture to cool before handling.
- Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Avoid direct water, liquid or metal contact.
- Do not exceed 110% of rated voltage.
- Do not use lamp if outer glass is scratched or broken.
- Use in enclosed fixture rated for this product.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Rated Life (MIN) **Primary Application**

Incandescent - Reflector R40 Medium Screw (E26) C-9 6.0 h Photofloods

PHOTOMETRIC CHARACTERISTICS

Center Beam Candlepower 5500.0 (CBCP) (NOM) Color Temperature (NOM) 3300.0 K

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	500.0
Voltage (NOM)	120.0

DIMENSIONS

Maximum Overall Length	6.630 in(168.4 mm)
(MOL) (NOM)	
Bulb Diameter (DIA) (NOM)	5.000 in(127.0 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

30145 DXC DXC Case 10043168301456 24 Unit 1 24

043168301459