





#### **CAUTIONS & WARNINGS**

### Caution

- Risk of Burn
- Allow lamp to cool before handling.
- Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Do not exceed 110% of rated voltage.

### **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament

**Bulb Finish** 

Rated Life (NOM)

Halogen - Single-Ended Τ4 **Double Contact Bayonet** (BA15d) CC-8 Clear 2000.0 h

# **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) 5000.0 Color Temperature (NOM) 2950.0 K Nominal Initial Lumens per Watt 20.0 (NOM)

**ELECTRICAL CHARACTERISTICS** 

	•••••••
Wattage (NOM)	250.0
Voltage (NOM)	120.0

### DIMENSIONS

Maximum Overall Length 3.000 in(76.2 mm) (MOL) (NOM) Bulb Diameter (DIA) (NOM) Light Center Length (LCL) (NOM)

0.500 in(12.7 mm) 1.625 in(41.3 mm)

# **PRODUCT INFORMATION**

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

43697 Q250CL/DC ESS Case 10043168436974 6 Unit 1 6

043168436977