



GE
Lighting

20330 - 45R/FL/MI-1 6PK

GE soft white 45 watt R30 floodlight 1-pack

- Use original GE's Soft White when you need a light without glare and harsh shadows.
- Replace ordinary light bulbs with GE Flood and Spotlight in all your track and recessed lighting fixtures.
- 2600K soft white light appearance
- Estimated yearly energy costs \$5.42 based on 3 hours per day \$0.11 per kWh
- GE soft white indoor spotlights provide warm, pleasing everyday light without harsh glares and shadows. These bulbs' funnel shape and reflective coating help direct light where it is needed better than a standard incandescent bulb
- Lasts 1.8 years based on 3 hours per day usage
- R30 indoor floodlight with medium base for use in directional fixtures such as recessed can lighting
- 425 lumens providing cozy, relaxing™ light

Energy Savings

Photo
Not Available

Wattage

Reduced

Photo
Not Available

Photo
Not Available



GENERAL CHARACTERISTICS

Lamp Type	Incandescent - Reflector
Bulb	BR30
Base	Medium Screw (E26)
Filament	CC-6
Rated Life (NOM)	2000.0 h
Life in Years (NOM)	1.8
Primary Application	Indoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	425.0
Center Beam Candlepower (CBCP) (NOM)	300.0
Color Temperature (NOM)	2600.0 K
Nominal Initial Lumens per Watt (NOM)	10.77778

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	45.0
Voltage (NOM)	120.0
Estimated Energy Cost per Year (NOM)	5.42

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.370 in(136.4 mm)
Bulb Diameter (DIA) (NOM)	3.750 in(95.2 mm)

PRODUCT INFORMATION

Product Code	20330
Description	45R/FL/MI-1 6PK
Standard Package	BUNDLE
Standard Package GTIN	00043168203302
Standard Package Quantity	30
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	30
UPC	043168906791

CAUTIONS & WARNINGS

Warning

For additional information, visit www.gelighting.com

- Unexpected lamp rupture may cause injury, fire, or property damage
 - Avoid direct water, liquid or metal contact.
- Risk of Fire
 - Keep combustible materials away from lamp.