

DuraMax Reflector Spot

DuraMax 65W 120V BR-30 SP 20D /LL 1CT

Philips DuraMax® Long Life Light Bulbs reduce the hassle of replacing light bulbs every few months, since all DuraMax products last longer than standard incandescent light bulbs. A wide assortment of shapes, sizes and wattages ensure that there is a DuraMax product to meet most basic lighting needs.

Product data

• General Characteristics

Base	Medium [Single Contact Medium
	Screw]
Base Information	Aluminum [Aluminum Base]
Bulb	BR30
Bulb Finish	Clear
Filament Shape	CC6 [Straight]
Operating Position	Base Up Horizontal (BUH) [Hanging
	+/-90D or Base Up HOR (BUH)]
Main Application	Indoor Reflector
Atmosphere	Gas
Life with 3h/day use	2.3 an
[years]	
Estimated Energy	7.83 \$
Cost/YR	

• Light Technical Characteristics

Beam Description	Spot
Beam Angle	20 D
Color Temperature	2710 K
Initial lumen	620 Lm

• Electrical Characteristics

Watts	65 W
Voltage	120 V

• Product Dimensions

Max Overall Length	5.375 (max) in
(MOL) - C	

Diameter D

Footnotes
Footnotes Incandes cent

87 [Do not allow hot bulb to come in contact with liquid or metal parts of the fixture, as glass may shatter. Do not use outdoors. Do not operate in close proximity to flammable materials or those adversely affected by heat or drying. Operate only in heat resistant sockets. (87)]

• Product Data

Product number Full product name

Short product name


Pieces per Sku eop_pck_cfg Skus/Case Bar code on pack Bar code on case Logistics code(s) eop_net_weight_pp 167692 DuraMax 65W 120V BR-30 SP 20D /LL 1CT DuraMax 65W 120V BR-30 SP 20D /LL 1CT 1 12

12 46677167691 50046677167696 920681836309 0.001 kg

3.75 in



Dimensional drawing







E26



 $\ensuremath{\mathbb{C}}$ 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting