




GE
Lighting

72532 - 150A21/RS-PK6

GE rough service work light 150/133 watt A21 1-pack

- 130/120 volts
- A21 shape with medium base for use in rough service applications
- GE rough services worklight bulbs are specially designed with rugged filaments and mounts to withstand rough handling and shock better than regular household bulbs
- Lasts 0.9/2.4 years based on 3 hours per day usage
- Estimated yearly energy costs \$18.07/\$16.02 based on 3 hours per day \$0.11 per kWh
- Provides 2065/1580 lumens

Photo
Not Available



GENERAL CHARACTERISTICS

| | |
|---------------------|-----------------------|
| Lamp Type | Incandescent - A-line |
| Bulb | A21 |
| Base | Medium Screw (E26) |
| Filament | C-17 |
| Bulb Finish | Inside frost |
| Rated Life (NOM) | 1000.0/2600.0 h |
| Primary Application | Rough Service |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------------|-------------------|
| Initial Lumens (NOM) | 2065.0 /1580.0 |
| Nominal Initial Lumens per Watt (NOM) | 13.76667 /11.8797 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|-------|
| Wattage (NOM) | 150.0 |
| Voltage (NOM) | 130.0 |

DIMENSIONS

| | |
|------------------------------------|--------------------|
| Maximum Overall Length (MOL) (NOM) | 5.370 in(136.4 mm) |
| Bulb Diameter (DIA) (NOM) | 3.750 in(95.2 mm) |
| Light Center Length (LCL) (NOM) | 4.060 in(103.1 mm) |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 72532 |
| Description | 150A21/RS-PK6 |
| Standard Package | BUNDLE |
| Standard Package GTIN | 00043168725323 |
| Standard Package Quantity | 30 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 30 |
| UPC | 043168725316 |