

# Rough / Vibration Service

## 150W 120-130V A21 FR RVBRS 2WR

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications.Rough Service incandescent lamps have an exceptionally strong filament for which a special filament wire is used, which makes these lamps extremely suitable for places where shocks, bumps and vibrations frequently occur. The clear version, with its completely visible filament, is a brilliant light source, whereas the inside-frosted lamp is used wherever well diffused light is required.

### Product data

#### • General Characteristics

| Base               | Medium [Single Contact Medium<br>Screw] |
|--------------------|---|
| Base Information   | Brass [Brass Base]                      |
| Bulb               | A21                                     |
| Bulb Finish        | Frosted                                 |
| Filament Shape     | Reinforced Construction [Reinforced]    |
| Operating Position | Universal [Any or Universal (U)]        |
| Main Application   | Rough & Vibration Service               |
| Atmosphere         | Gas                                     |
| Nominal Lifetime   | 1000 hr                                 |
| Rated Lifetime     | 1000 hr                                 |
| (hours)            |   |
| Rated Avg. Life @  | 1700 hr                                 |
| 120v               |   |

#### • Light Technical Characteristics

| Initial lumen    | 2205 Lm |
|------------------|---------|
| Initial Lumens @ | 1915 Lm |
| 120V             |         |


#### • Electrical Characteristics

| Watts        | 150 VV    |
|--------------|-----------|
| Lamp Wattage | 141 W     |
| Rated@120V   |           |
| Voltage      | 120-130 V |

| Starting Time   | 0.0 s                             |  |  |  |  |
|---|-----------------------------------|--|--|--|--|
| Environmental Characteristics     Energy Efficiency E |                                   |  |  |  |  |
| Label (EEL)   | -                                 |  |  |  |  |
| <ul> <li>Product Dimensions</li> </ul>                |                                   |  |  |  |  |
| Max Overall Length<br>(MOL) - C                       | 5.313 (max) in                    |  |  |  |  |
| Diameter D  | 2.625 in                          |  |  |  |  |
| • Product Data  |                                   |  |  |  |  |
| Product number  | 275784                            |  |  |  |  |
| Full product name                                     | 150W 120-130V A21 FR RVBRS<br>2WR |  |  |  |  |
| Short product name                                    | 150W 120-130V A21 FR RVBRS<br>2WR |  |  |  |  |
| Pieces per Sku  | 1                                 |  |  |  |  |
| eop_pck_cfg   | 60                                |  |  |  |  |
| Skus/Case<br>Bar code on pack                         | 60<br>46677275785                 |  |  |  |  |
| Bar code on case                                      | 50046677275780                    |  |  |  |  |
| Logistics code(s)                                     | 925287435502                      |  |  |  |  |
| eop_net_weight_pp                                     | 0.001 kg                          |  |  |  |  |



## Dimensional drawing



A21



E26



| Product                      | C (Max) | D (Norm) | D (Max) |
|------------------------------|---------|----------|---------|
| RC 150W E26 120-130V A-21 FR | -       | -        | -       |



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting