





GE
Lighting

20858 - Q20MR16C/CG15ESX

GE ConstantColor® Precise™ MR16

- UV protection



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
 - Allow lamp/fixture to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use in fixture rated for this product.

GENERAL CHARACTERISTICS

Lamp Type	Halogen - MR
Bulb	MR16
Base	2-Pin (GU5.3)
Filament	C-6
Rated Life (NOM)	5000.0 h
Lamp Enclosure Type (LET)	Covered glass

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	225.0
Center Beam Candlepower (CBCP) (NOM)	3150.0
Color Temperature (NOM)	2900.0 K
Beam Spread (NOM)	15.0 °

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	20.0
Voltage (NOM)	12.0
Burn Position	Universal burning position

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	1.875 in(47.6 mm)
Bulb Diameter (DIA) (NOM)	2.000 in(50.8 mm)

PRODUCT INFORMATION

Product Code	20858
Description	Q20MR16C/CG15ESX
ANSI Code	ESX
Standard Package	BUNDLE
Standard Package GTIN	00043168208581
Standard Package Quantity	20
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
UPC	043168992961