


# 41489 - Q50MR16/CCG40

GE MR16

UV protection





#### **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Burn
- Allow lamp/fixture to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in fixture rated for this product.

#### **GENERAL CHARACTERISTICS**

Lamp TypeHalogen - MRBulbMR16Base2-Pin (GU5.3)FilamentCC-6Rated Life (NOM)4000.0 hLamp Enclosure Type (LET)Covered glass

#### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) Center Beam Candlepower (CBCP) (NOM) Color Temperature (NOM) Beam Spread (NOM)

2950.0 K 40.0 °

615.0

1570.0

#### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)50.0Voltage (NOM)24.0Burn PositionUniversal burning position

### DIMENSIONS

Maximum Overall Length 1.875 in (MOL) (NOM) Bulb Diameter (DIA) (NOM) 2.000 in

## **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 1.875 in(47.6 mm) 2.000 in(50.8 mm)

043168414890