



Product 58308

Number:

Order 50MR16/T/NFL25/C(EXZ) 12V

Abbreviation:

General Tungsten Halogen Tru-Aim MR16 TITAN Axial Filament UV-
Description: Filter Hard Dichroic Reflector Cover Glass GU5.3 Bi-Pin Base
 50Watt 12Volt NFL Beam

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	50MR16TNFL25CEXZ 12V 20/CS 1/SKU
ANSI Code	EXZ
Average Rated Life (hr)	4000
Base	GU5.3 Bipin
Beam Angle (deg)	24
Beam Type	FL
Bulb	MR16
Centerbeam Candlepower (cp)	4400
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	2.008
Diameter (mm)	51.00
Ecologic	YES
Family Brand Name	TRU-AIM TITAN®
Filament	AXIAL
Horizontal Beam Angle (deg)	25
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	45.0
Nominal Voltage (V)	12.00
Nominal Wattage (W)	50.00
Vertical Beam Angle (deg)	25



Footnotes

- Max. seal temperature 370 C (662F)
- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector.

- Max pin temperature 220 C.
- Max temperature at lens reflector joint 240 C.
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.